

BookletChart™


Snake River – Lake Sacajawea

NOAA Chart 18545




A reduced-scale NOAA nautical chart for small boaters

When possible, use the full-size NOAA chart for navigation.



- Complete, reduced-scale nautical chart
- Print at home for free
- Convenient size
- Up-to-date with Notices to Mariners
- Compiled by NOAA's Office of Coast Survey, the nation's chartmaker



Published by the
National Oceanic and Atmospheric Administration
National Ocean Service
Office of Coast Survey
www.NauticalCharts.NOAA.gov
888-990-NOAA

What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

What is a BookletChart™?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at <http://www.NauticalCharts.NOAA.gov>.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

Notice to Mariners Correction Status

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.

For latest Coast Pilot excerpt visit the Office of Coast Survey website at <http://www.nauticalcharts.noaa.gov/nsd/searchbychart.php?chart=18545>.



(Selected Excerpts from Coast Pilot)

Snake River, 283 (325.2) miles above the mouth of Columbia River, rises in Yellowstone National Park, from which it winds S past the Grand Tetons, and thence for some 868 miles to its junction with the Columbia at Pasco, WA. From that junction for 119 (137) miles to Lewiston, ID there are few small-craft facilities. (See small-craft facilities tabulation on charts 18545, 18546, 18547, and 18548 for supplies and services available.) There are several

marinas along the river at **Clarkston**, WA and **Lewiston**, ID where berths, gasoline, diesel fuel, water, ice, and marine supplies may be obtained.

The Ports of Clarkston and Lewiston at the confluence of the Snake and Clarkford Rivers are the primary ports along the Snake River and serve the inland agricultural and logging communities of Washington, Idaho, and Oregon. Barge loading facilities and grain terminals are available at both ports.

Near its mouth, at the village of **Burbank**, Snake River is crossed by the Burlington Northern Railroad lift bridge with a clearance of 14 feet down and 60 feet up. The bridgetender monitors VHF-FM channel 16 and works on channel 13; call sign KQ- 9047. About 0.6 (0.7) mile above the railroad bridge, there are dual spans of a fixed highway bridge with a least clearance of 61 feet. Numerous overhead cables with a reported minimum clearance of 43 feet cross Snake River between the fixed highway bridge and Ice Harbor Lock and Dam.

East Pasco, on the N side of Snake River 1 mile above the mouth, has privately owned facilities for receipt and shipment of petroleum products and liquid fertilizer. Burbank, on the S side of the river has two grain facilities owned by the Port of Walla Walla and operated by private companies. From East Pasco to Lewiston there are several facilities used for shipment of grain and wood chips. Other facilities along the river specialize in the receipt and shipment of logs, general cargo, petroleum products, anhydrous ammonia, and liquid fertilizer.

Ice Harbor Lock and Dam, 8.4 (9.7) miles above the mouth of the Snake River, has a single lift lock with a vertical lift of about 100 feet. A **restricted area** is above and below the dam; the area is marked by buoys above the dam. (See **207.718**, chapter 2, for information concerning use, administration, and navigation of Ice Harbor Lock and Dam.) **Lake Sacajawea**, the lake formed by the waters behind Ice Harbor Dam, provides depths at slack water of 10 feet or more for a distance of 27.8 (32) miles to Lower Monumental Dam.

Lower Monumental Lock and Dam, 27.6 (31.8) miles above Ice Harbor Dam and about 36 (41.5) miles above the mouth of the Snake River, has a single lift lock with a vertical lift of about 100 feet. A **restricted area** is above and below the dam; the area is marked by buoys above the dam. (See **207.718**, chapter 2, for information concerning use, administration, and navigation of Lower Monumental Lock and Dam.)

The Snake River between Lower Monumental Dam and Little Goose Dam, 25 (28.8) miles above Lower Monumental Dam, is crossed by three fixed bridges with a least clearance of 52 feet; overhead power cables crossing the river between the two dams have a clearance of 90 feet.

Little Goose Lock and Dam, about 25 (28.8) miles above Lower Monumental Dam and about 61.1 (70.3) miles above the mouth of the Snake River, has a single lift lock with a vertical lift of about 98 feet. A **restricted area** is above and below the dam; the area is marked by buoys above the dam. (See **207.718**, chptr 2, for information concerning use, administration, and navigation of Little Goose Lock and Dam.)

Lake Bryan, the pool formed by Little Goose Dam is crossed by a fixed highway bridge with a clearance of 60 feet about 10.7 (12.3) miles above the dam; overhead power cables with a least clearance of 75 feet cross the lake between Little Goose Dam and Lower Granite Dam.

Lower Granite Lock and Dam, about 31.5 (36.8) miles above Little Goose Dam and about 93.4 (107.5) miles above the mouth of the Snake River, has a single lift navigation lock 675 feet long and 86 feet wide. The dam, completed in 1975, permits navigation to **Lewiston**, Idaho, 120 (138) miles above the mouth of the Snake River. A **restricted area** is above and below the dam; the area is marked by buoys above the dam. (See **207.718**, chapter 2, for information concerning use, administration, and navigation of Lower Granite Lock and Dam.)

U.S. Coast Guard Rescue Coordination Center 24 hour Regional Contact for Emergencies

RCC Seattle

Commander

13th CG District

Seattle, WA

(206) 220-7001

Table of Selected Chart Notes

Corrected through NM Sep. 20/03
Corrected through LNM Sep. 2/03

The Project Depth of 14ft is based on the minimum operating pool elevation of 335ft.

All craft should avoid areas where the skin divers flag, a red square with a diagonal white stripe, is displayed.

CAUTION

Small craft should stay clear of large commercial and government vessels even if small craft have the right-of-way.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.507" southward and 3.992" westward to agree with this chart.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

NOAA VHF-FM WEATHER BROADCASTS

The National Weather Service station listed below provides continuous marine weather broadcasts. The range of reception is variable, but for most stations is usually 20 to 40 miles from the antenna site.

Pendleton, OR WXL-95 162.55 MHz

LOWER SNAKE RIVER DAMS ICE HARBOR LOWER MONUMENTAL LITTLE GOOSE LOWER GRANITE

These four Snake River Dams were authorized by Congress to serve the Pacific Northwest as "Multipurpose" projects, providing electric power, slack-water transportation to the Pacific Ocean Ports, and to retain passage for anadromous fish to and from their habitual spawning waters inland.

Many parks and recreation areas are also planned by the Corps of Engineers for the enjoyment of the entire family. Northwest residents and their guests will have ready access to swimming, boating, fishing, skiing and picnicking.

ANCHOR CABLES

Submerged cables, marked by steel bouys, anchor the end and middle of log boom to deadmen.

Minimum clearance over cable to north and east of marker buoy is 16 feet.

The anchor cable from the middle of log boom is not marked.

HEIGHTS

Heights are in feet. Contour elevations refer to mean sea level.

RULES OF THE ROAD (ABRIDGED)

Motorless craft have the right-of-way in almost all cases. Sailing vessels and motorboats less than sixty-five feet in length shall not hamper, in a narrow channel, the safe passage of a vessel which can navigate only inside that channel.

A motorboat being overtaken has the right-of-way.

Motorboats approaching head to head or nearly so should pass port to port.

When motorboats approach each other at right angles or obliquely, the boat on the right has the right-of-way in most cases.

Motorboats must keep to the right in narrow channels when safe and practicable.

Mariners are urged to become familiar with the complete text of the Rules of the Road in U.S. Coast Guard publication "Navigation Rules."

MERCATOR PROJECTION SCALE 1:20,000 at 46°23'

North American Datum of 1983
(World Geodetic System 1984)

SNAKE RIVER

Mileage distances along the Snake River are in Statute Miles. Distances along the Snake River are from the junction of the Columbia River and are indicated thus: —◆—

Tables for converting Statute Miles to International Nautical miles are given in Coast Pilot 7.

THE SNAKE RIVER FACTS AND HISTORY

The Snake River, one of the most important streams in the Pacific northwest section of the United States, is the largest tributary of the Columbia River. The river rises in high, rugged mountains of the continental divide near the southwest corner of Yellowstone National Park in Wyoming and joins the Columbia near Pasco, Washington after flowing 1,038 miles. The river descends from elevations of 10,000 feet to an elevation of 300 feet. Discovered in 1805 by the Lewis and Clark expedition, the Snake River with its many turbulent rapids presented one of the most difficult rivers for the Expedition to negotiate. Canoes were damaged by rocks, supplies became salvaged and some supplies were lost when a canoe capsized. Today, near Pasco-Kennewick, Sacajawea State Park and museum is dedicated to the Indian woman who guided the explorers.

CAUTION

The water level in the upper pool above Ice Harbor Dam may fluctuate without warning between 437 feet MSL (pool low water elevation) and the 440 feet MSL (normal pool) sounding datum.

Mariners are advised to use caution due to possible change in water level.

SOUNDINGS AND OVERHEAD CLEARANCES IN FEET

Soundings and vertical clearances of bridges and overhead cables are referred to the respective normal pool levels which are 340 feet above mean sea level in the lower pool and 440 feet in the upper pool above Ice Harbor Dam.

CAUTION

The depths of water on this chart have been determined from conditions existing prior to the filling of the pool. Shallower depths than charted may exist within the blue tinted areas, particularly near the shoreline.

CAUTION

The water level in the upper pool above Ice Harbor Dam may fluctuate without warning between 437 feet MSL (pool low water elevation) and the 440 feet MSL (normal pool) sounding datum.

Mariners are advised to use caution due to possible change in water level.

FACILITIES

Locations of public marine facilities are shown by large magenta numbers with leaders and refer to the facility tabulation.

COLUMBIA AND SNAKE RIVERS

Mileage distances along the Columbia and Snake Rivers are in Statute Miles. Distances along the Columbia River are eastward from the mouth, and the Snake River are eastward from the junction of the Columbia River and are indicated thus: —◆—

Tables for converting Statute Miles to International Nautical miles are given in Coast Pilot 7.

WARNINGS CONCERNING LARGE VESSELS

The "Rules of The Road" state that recreational boats shall not impede the passage of a vessel that can navigate only within a narrow channel or fairway. Large vessels may appear to move slowly due to their large size, but actually transit at speeds in excess of 12 knots, requiring a great distance in which to maneuver or stop. A large vessel's superstructure may block the wind with the result that sailboats and sailboards may unexpectedly find themselves unable to maneuver. Bow and stern waves can be hazardous to small Vessels. Large vessels may not be able to see small craft close to their bows.

LOWER SNAKE RIVER DAMS

ICE HARBOR
LOWER MONUMENTAL
LITTLE GOOSE
LOWER GRANITE

These four Snake River Dams were authorized by Congress to serve the Pacific Northwest as "Multipurpose" projects, providing electric power, slack-water transportation to the Pacific Ocean Ports, and to retain passage for anadromous fish to and from their habitual spawning waters inland.

Many parks and recreation areas are also planned by the Corps of Engineers for the enjoyment of the entire family. Northwest residents and their guests will have ready access to swimming, boating, fishing, skiing and picnicking.

THE SNAKE RIVER FACTS AND HISTORY

The Snake River, one of the most important streams in the Pacific northwest section of the United States, is the largest tributary of the Columbia River.


The river rises in high, rugged mountains of the continental divide near the southwest corner of Yellowstone National Park in Wyoming and joins the Columbia near Pasco, Washington after flowing 1,038 miles. The river descends from elevations of 10,000 feet to an elevation of 300 feet.

Discovered in 1805 by the Lewis and Clark expedition, the Snake River with its many turbulent rapids presented one of the most difficult rivers for the Expedition to negotiate. Canoes were damaged by rocks, supplies became saturated and some supplies were lost when a canoe capsized.

Today, near Pasco-Kennewick, Sacajawea State Park and museum is dedicated to the Indian woman who guided the explorers.

The water level
warning between
(normal pool) and
Mariners are

Mileage
Distances
River and
Tables
are given




4

Note: Chart grid
lines are aligned
with true north.

Printed at reduced scale.

SCALE 1:20,000
Nautical Miles

See Note on page 5.




CAUTION

level in the upper pool above Ice Harbor Dam may fluctuate without
 een 437 feet MSL. (pool low water elevation) and the 440 feet MSL.
) sounding datum.
 re advised to use caution due to possible change in water level.


SNAKE RIVER

ge distances along the Snake River are in Statute Miles.
 es along the Snake River are from the junction of the Columbia
 nd are indicated thus: ————
 s for converting Statute Miles to International Nautical miles
 an in Coast Pilot 7.




This BookletChart was reduced to 75% of the original chart scale.
 The new scale is 1:26667. Barscales have also been reduced and
 are accurate when used to measure distances in this BookletChart.

Topographic map of the Aband Air Strip area. The map shows contour lines with elevations ranging from 900 to 1400 feet. A river flows through the center of the map. A railroad line, labeled 'BN RR', runs horizontally across the lower right portion of the map. The 'Aband Air Strip' is indicated by a dashed line. A 'Gaging Sta' is marked with a pink dot and labeled '43 R N 38°'. The map includes a scale bar for 1 mile and a north arrow. The map is labeled 'Joins page 5' on the left and 'Joins page 12' at the bottom.



This BookletChart has been updated through: Coast Guard Local Notice To Mariners: 4812 11/27/2012,
 NGA Weekly Notice to Mariners: 4812 12/1/2012,
 Canadian Coast Guard Notice to Mariners: 0912 9/28/2012.




8

Note: Chart grid lines are aligned with true north.

Printed at reduced scale.


SCALE 1:20,000
Nautical Miles

See Note on page 5.





WASHINGTON SNAKE RIVER LAKE SACAJAWEA



ICE HARBOR DAM

Photo Courtesy U.S. CORPS OF ENGINEERS

Chart 18545 15th Ed., Sep./03 ■ Corrected through NM Sep. 20/03
Corrected through LNM Sep. 2/03





NSN 7642014011625
NIMA REFERENCE NO. 18XHA18545




ED NO. 15

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY



Joins page 15 Regulations (see note A)

SIDE B



18545 15th Ed., Sep./03 ■ Corrected through NM Sep. 20/03
Corrected through LNM Sep. 2/03

MERCATOR PROJECTION SCALE 1:20,000 at 46°23'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS AND OVERHEAD CLEARANCES IN FEET

Soundings and vertical clearances of bridges and overhead cables are referred to the respective normal pool levels which are 340 feet above mean sea level in the lower pool and 440 feet in the upper pool above Ice Harbor Dam.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

CAUTION
Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

Joins page 16

CAUTION


10


Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

SCALE 1:20,000
Nautical Miles

See Note on page 5.





PLANE COORDINATE GRID
(based on NAD 1927)


Washington State Grid south zone, is indicated by dashed ticks at 5,000 foot intervals. The last three digits are omitted.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

WARNINGS CONCERNING LARGE VESSELS

The "Rules of The Road" state that recreational boats shall not impede the passage of a vessel that can navigate only within a narrow channel or fairway. Large vessels may appear to move slowly due to their large size, but actually transit at speeds in excess of 12 knots, requiring a great distance in which to maneuver or stop. A large vessel's superstructure may block the wind with the result that sailboats and sailboards may unexpectedly find themselves unable to maneuver. Bow and stern waves can be hazardous to small Vessels. Large vessels may not be able to see small craft close to their



RULES OF THE ROAD (ABRIDGED)

Motorless craft have the right-of-way in almost all cases.
Sailing vessels and motorboats less than sixty-five feet in length shall not hamper, in a narrow channel, the safe passage of a vessel which can navigate only inside that channel.

A motorboat being overtaken has the right-of-way.
Motorboats approaching head to head or nearly so should pass port to port.

When motorboats approach each other at right angles or obliquely, the boat on the right has the right-of-way in most

Joins page 18


12


Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

SCALE 1:20,000
Nautical Miles

See Note on page 5.









ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)

Joins page 19

SAFETY HINTS

1. Keep your chart up to date by applying all Notices to Mariners corrections when you receive them.
2. Read carefully all notes printed on your chart, each is vital to your safety afloat.
3. Learn the meaning of each symbol and abbreviation on your chart from Chart No. 1.
4. The compass on your chart shows the variation from true north, however you must also correct your bearing for the deviation of your





SIDE B

JOINS CHART 18546 (SIDE A)

18545

NO	LOCATION	TIDES		DEPTH		SERVICES				SUPPLIES			
		LOW	HIGH	LOW	HIGH	BOAT RENTAL	CHARTER HOUSE/BOAT	FOOD LODGING CAMPING	TOILET SHOWER LAUNDRY	WATER SUPPLY	WATER SUPPLY	WATER SUPPLY	WATER SUPPLY
1	SACAJAWEA ST PK					6	8	8	8				T
4	LEVEE PARK					7	7	7	7				TS

Joins page 21

18545 15th Ed., Sep. /03 ■ Corrected through NM Sep. 20/03
Corrected through LNM Sep. 2/03

MERCATOR PROJECTION SCALE 1:20,000 at 46°23'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS AND OVERHEAD CLEARANCES IN FEET

Soundings and vertical clearances of bridges and overhead cables are referred to the respective normal pool levels which are 340 feet above mean sea level in the lower pool and 440 feet in the upper pool above Ice Harbor Dam.

HEIGHTS

Heights are in feet. Contour elevations refer to mean sea level.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 7 for important supplemental information

CAUTION

This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Imagery and Mapping Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner.

CAUTION

The water level in the upper pool above Ice Harbor Dam may fluctuate without warning between 437 feet MSL, (pool low water elevation) and the 440 feet MSL, (normal pool) sounding datum.

Mariners are advised to use caution due to possible change in water level.

CAUTION

The depths of water on this chart have been determined from conditions existing prior to the filling of the pool. Shoaler depths than charted may exist within the blue tinted areas, particularly near the shoreline.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

CAUTION

Small craft should stay clear of large commercial and government vessels even if small craft have the right-of-way.



All craft should avoid areas where the skin divers flag, a red square with a diagonal white stripe, is displayed.


WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.





PLANE COORDINATE GRID (based on NAD 1927)

Washington State Grid south zone, is indicated by dashed ticks at 5,000 foot intervals. The last three digits are omitted.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

COLUMBIA AND SNAKE RIVERS

Mileage distances along the Columbia and Snake Rivers are in Statute Miles. Distances along the Columbia River are eastward from the mouth, and the Snake River are eastward from the junction of the Columbia River and are indicated thus: —●—

Tables for converting Statute Miles to International Nautical miles are given in Coast Pilot 7.

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 7. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 13th Coast Guard District in Seattle, Washington or at the Office of the District Engineer, Corps of Engineers in Walla Walla, Washington.

Refer to charted regulation section numbers.

PRINT-ON-DEMAND CHARTS

This chart is available in a version updated weekly by NOAA for Notices to Mariners and critical corrections. Charts are printed when ordered using Print-on-Demand technology. New Editions are available 5-8 weeks before their release as traditional NOAA charts. Ask your chart agent about print-on-Demand charts.

WARNINGS CONCERNING LARGE VESSELS

The "Rules of The Road" state that recreational boats shall not impede the passage of a vessel that can navigate only within a narrow channel or fairway. Large vessels may appear to move slowly due to their large size, but actually transit at speeds in excess of 12 knots, requiring a great distance in which to maneuver or stop. A large vessel's superstructure may block the wind with the result that sailboats and sailboards may unexpectedly find themselves unable to maneuver. Bow and stern waves can be hazardous to small vessels. Large vessels may not be able to see small craft close to their bows.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.507" southward and 3.992" westward to agree with this chart.


FACILITIES


Locations of public marine facilities are shown by large magenta numbers with leaders and refer to the facility tabulation.

NOAA VHF-FM WEATHER BROADCASTS

The National Weather Service station listed below provides continuous marine weather broadcasts. The range of reception is variable, but for most stations is usually 20 to 40 miles from the antenna site.

Pendleton, OR WXL-95 162.55 MHz





Joins page 12

RULES OF THE ROAD (ABRIDGED)

Motorless craft have the right-of-way in almost all cases.
Sailing vessels and motorboats less than sixty-five feet in length shall not hamper, in a narrow channel, the safe passage of a vessel which can navigate only inside that channel.
A motorboat being overtaken has the right-of-way.
Motorboats approaching head to head or nearly so should pass port to port.
When motorboats approach each other at right angles or obliquely, the boat on the right has the right-of-way in most cases.
Motorboats must keep to the right in narrow channels when safe and practicable.
Mariners are urged to become familiar with the complete text of the Rules of the Road in U.S. Coast Guard publication "Navigation Rules."



NOTE B

Significant shoaling consisting of numerous rocks and boulders has been reported in the Snake River.

Additional information can be obtained at nauticalcharts.noaa.gov

Joins page 17


Formerly 682-SC, 1st Edition, 196



Joins page 24

18

Note: Chart grid lines are aligned with true north.



ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)
Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical	G green	Mo morse code	R TR radio tower
Al alternating	IQ interrupted quick	N nun	Rot rotating
B black	Iso isophase	OBSC obscured	s seconds
Bn beacon	LT HO lighthouse	Oc occulting	SEC sector
C can	M nautical mile	Or orange	St M statute miles
DIA diaphone	m minutes	Q quick	VQ very quick
F fixed	MICRO TR microwave tower	R red	W white
Fl flashing	Mkr marker	Ra Ref radar reflector	WHIS whistle
		R Bn radiobeacon	Y yellow

Bottom characteristics:

Blds boulders	Co coral	gy gray	Oys oysters	so soft
bk broken	G gravel	h hard	Rk rock	Sh shells
Cy clay	Grs grass	M mud	S sand	sy sticky

Miscellaneous:


AUTH authorized	Obstr obstruction	PD position doubtful	Subm submerged
ED existence doubtful	PA position approximate	Rep reported	
(2) Wreck, rock, obstruction, or shoal swept clear to the depth indicated.			
(2) Rocks that cover and uncover, with heights in feet above datum of soundings.			



SAFETY HINTS

1. Keep your chart up to date by applying all Notices to Mariners corrections when you receive them.
2. Read carefully all notes printed on your chart, each is vital to your safety afloat.
3. Learn the meaning of each symbol and abbreviation on your chart from Chart No. 1.
4. The compass on your chart shows the variation from true north, however you must also correct your bearing for the deviation of your boat.
5. Constantly use your chart from the beginning to end of each trip. Keep in mind the orientation of your boat with respect to the chart.
6. Maintain your position on the chart by relating charted features with those you can identify in your surroundings.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

963 KAPP 1771







Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

~~SCALE 1:20,000~~
Nautical Miles

See Note on page 5.






18545

NO	LOCATION	TIDES	DEPTH	SERVICES				SUPPLIES			
				REPAIRS	BOAT RENTAL	FOOD LODGING CAMPING	WATER	WATER	WATER	WATER	WATER
1	SACAJAWEA ST PK			6	8	B	S				
4	LEVEY PARK			7	7	S					
8	MATTHEWS			4	4	S					


(+)(DENOTES HOURS LATER) (DENOTES HOURS EARLIER)
 THE LOCATIONS OF THE ABOVE PUBLIC MARINE FACILITIES ARE SHOWN ON THE CHART BY LARGE MAGENTA NUMBERS.
 THE TABULATED "APPROACH-DEPT(REPORTED)" IS THE DEPTH AVAILABLE FROM THE NEAREST NATURAL OR DREDGED CHANNEL TO THE FACILITY.
 THE TABULATED "PUMPING STATION" IS DEFINED AS FACILITIES AVAILABLE FOR PUMPING OUT BOAT HOLDING TANKS.



JOINS SIDE B

SIDE A

JOINS CHART 18542



18545 15th Ed., Sep./03 Corrected through NM Sep. 20/03
Corrected through LNM Sep. 2/03


22


Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

SCALE 1:20,000
Nautical Miles



See Note on page 5.







Joins page 17


Joins page 24







Note: Chart grid lines are aligned with true north.





18545



VHF Marine Radio channels for use on the waterways:

Channel 6 – Inter-ship safety communications.

Channel 9 – Communications between boats and ship-to-coast.

Channel 13 – Navigation purposes at bridges, locks, and harbors.

Channel 16 – Emergency, distress and safety calls to Coast Guard and others, and to initiate calls to other

vessels. Contact the other vessel, agree to another channel, and then switch.

Channel 22A – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here.

Channels 68, 69, 71, 72 and 78A – Recreational boat channels.

Getting and Giving Help — Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.

Distress Call Procedures

- Make sure radio is on.
- Select Channel 16.
- Press/Hold the transmit button.
- Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of Emergency; Number of People on Board.
- Release transmit button.
- Wait for 10 seconds — If no response Repeat MAYDAY call.

HAVE ALL PERSONS PUT ON LIFE JACKETS!



NOAA Weather Radio All Hazards (NWR) is a nationwide network of radio stations broadcasting continuous weather information directly from the nearest National Weather Service office. NWR broadcasts official Weather Service warnings, watches, forecasts and other hazard information 24 hours a day, 7 days a week.

<http://www.nws.noaa.gov/nwr/>

Quick References

Nautical chart related products and information	—	http://www.nauticalcharts.noaa.gov
Online chart viewer	—	http://www.nauticalcharts.noaa.gov/mcd/NOAAChartViewer.html
Report a chart discrepancy	—	http://ocsddata.ncd.noaa.gov/idrs/discrepancy.aspx
Chart and chart related inquiries and comments	—	http://ocsddata.ncd.noaa.gov/idrs/inquiry.aspx?frompage=ContactUs
Chart updates (LNM and NM corrections)	—	http://www.nauticalcharts.noaa.gov/mcd/updates/LNM_NM.html
Coast Pilot online	—	http://www.nauticalcharts.noaa.gov/nsd/cpdownload.htm
Tides and Currents	—	http://tidesandcurrents.noaa.gov
Marine Forecasts	—	http://www.nws.noaa.gov/om/marine/home.htm
National Data Buoy Center	—	http://www.ndbc.noaa.gov/
NowCoast web portal for coastal conditions	—	http://www.nowcoast.noaa.gov/
National Weather Service	—	http://www.weather.gov/
National Hurricane Center	—	http://www.nhc.noaa.gov/
Pacific Tsunami Warning Center	—	http://ptwc.weather.gov/
Contact Us	—	http://www.nauticalcharts.noaa.gov/staff/contact.htm



— For the latest news from Coast Survey, follow @nauticalcharts



This Booklet chart has been designed for duplex printing (printed on front and back of one sheet). If a duplex option is not available on your printer, you may print each sheet and arrange them back-to-back to allow for the proper layout when viewing.

NOAA's Office of Coast Survey



The Nation's Chartmaker